TP-LINK[®]

150Mbps Universal WiFi Range Extender TL-WA750RE

• Features:

- Greatly extend existing wireless coverage to eliminate "dead zones"
- Work as a wireless network adapter, providing wireless connectivity for your Ethernet-enabled devices
- Wireless N speed up to 150Mbps
- Wall mount design, just plug in and play, very convenient
- Easily extend your wireless network at a push of the Range Extender button
- Profile function remembers previously connected wireless networks
- Supports domain name-based login (http://tplinkextender.net) for advanced management



• Description

TP-LINK's wall-mounted TL-WA750RE is designed to conveniently extend the coverage and improve the signal strength of an existing wireless network to eliminate "dead zones". Being incredibly user friendly, it is ideal for large homes or offices for experienced or novice users. Besides, TL-WA750RE can also be used as a wireless network adapter to help a wired device such as a smart TV or game console to receive Wi-Fi signals.

www.tp-link.com

• Specifications:

Hardware Features	
Wireless Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Interface	One 10/100Mbps Ethernet Port (RJ45)
Button	Range Extender Button, Reset Button
Antenna	Internal
Power Consumption	About 3W
Wireless Features	
Frequency	2.4~2.4835GHz
Signal Rate	11n: Up to 150Mbps(dynamic)
	11g: Up to 54Mbps(dynamic)
	11b: Up to 11Mbps(dynamic)
EIRP	< 20 dBm
Reception Sensitivity	130M: -68dBm@10% PER
	108M: -68dBm@10% PER
	54M: -68dBm@10% PER
	11M: -85dBm@8% PER
	6M: -88dBm@10% PER
Wireless Mode	1M: -90dBm@8% PER Range Extender
WITEIESS MIDDE	WMM(Wi-Fi Multimedia); Wireless MAC Address Filtering;
Wireless Functions	
Wireless Security	Wireless Statistic;Domain Login Function64/128/152-bit WEP WPA-PSK / WPA2-PSK
Others	04/120/152-bit WER WRA-FSK/ WRA2-FSK
Certification	CE. RoHS
System Requirements	Microsoft® Windows® 8/7/Vista™/XP/NT/98SE,
	Mac® OS, NetWare®, UNIX® or Linux.
Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40℃~70℃ (-40°F~158°F)
Operating Humidity	10%~90% non-condensing
Storage Humidity	5%~90% non-condensing.
Dimensions ($W \times D \times H$)	4.3 × 2.6 × 3.0in. (110.0 × 65.8 × 75.2mm)
Plug Type	EU

• Diagram:



Package:

- 150Mbps Universal WiFi Range Extender TL-WA750RE
- RJ-45 Ethernet Cable
- Resource CD
- Quick Installation Guide

Related Product:

- 150Mbps Wireless N ADSL2+ Modem Router TD -W8951ND
- 150Mbps Wireless N Nano USB Adapter TL-WN725N
- -150Mbps Wireless N PCI Adapter TL-WN751ND

Specifications are subject to change without notice. IPLINK is a registered trademark of IPLINK fechnologies Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications may be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from IPLINK fechnologies Co., Ltd. www.tp-link.com